



**NOTES**

1. CONCRETE - 4000 psi, AIR ENTRAINED
2. REINFORCING STEEL - GRADE 60, ASTM A-615 - REINFORCING BASED ON PENNDOT RC-46M
3. WELDED WIRE FABRIC - ASTM-A185
4. LADDER RUNGS - COPOLYMER POLYPROPYLENE PLASTIC w/1/2" REBAR, GRADE 60 WHEN NEEDED
5. MATERIAL AND CONSTRUCTION SHALL COMPLY WITH PENNDOT PUB. 408, 72, & RC46M
6. LOCATIONS OF PIPE OPENINGS AS REQUIRED
7. ALL MATERIAL USED MADE IN THE USA
8. TRAP/SNOUT - SEE ACCOMPANYING SPEC. SHEET

OPTIONAL JOINT  
(WHEN NEEDED)

REINFORCING PER  
RC-46M STANDARDS

BELL TRAP & HOOK  
LOCATED OVER PIPE

**SECTION A**

**PLAN VIEW**

**ALTOMARE PRECAST, INC.**  
4300 Wissahickon Ave.  
Philadelphia, PA 19129  
Ph: 215-225-8800 Fax: 215-225-8900

**TITLE:**  
**PENNDOT Type 5 Box  
w/ 6" Walls, Sump & Trap**

**PROJECT:**  
**CONTR:**  
**DATE:**